




Optem FUSION

Extreme Micro-Imaging
Versatility—Visible to SWIR
(400 -1700 nm)





About Excelitas Technologies

Excelitas is a leader in the global end markets of life sciences, advanced industries, next generation semiconductors and aerospace and defense, delivering advanced technologies that enrich life. Headquartered in Pittsburgh, Pennsylvania, USA, Excelitas is an essential partner in the design, development and manufacturing of photonic technologies, providing cutting-edge innovations in sensing, detection, imaging, optics and specialty lighting to customers worldwide. Excelitas is at the forefront of many relevant megatrends impacting the world today, including precision medicine, industrial automation, artificial intelligence, connected devices (IoT) and military modernization.

HIGH-PERFORMANCE... HIGH-MAGNIFICATION...LARGE WAVELENGTH RANGE

- Wafer Processing
- MEMS Development
- Non-contact Metrology
- Fiber Alignment
- Analytical Probing
- Solder Bump Inspection
- Filter & Particle Analysis
- Micro-hole Arrays
- Nanolithography
- Laser Machining / Marking
- Micro Structures
- Materials Research
- Micro Dispensing
- Well Plate Scanning
- Crystal Development
- Gemological Analysis
- Biomedical Research
- Microfluidics



Introduction

Extreme Micro-Imaging Versatility

The all new Optem FUSION Lens System incorporates expanded functionality, bi-directional infinity optics, and a uniform modular matrix to provide OEMs with the ideal lens solution for streamlined integration of high-magnification imaging across the key Visible (400 nm - 700 nm), NIR (700 nm - 1100nm) and SWIR (900 nm - 1700 nm) wavelength ranges.

Simply change-out modules to modify the form, function and performance of your Optem FUSION Lens System to meet the exact wavelength range, spatial, functional, mounting and imaging requirements of your system.

OEM-Optimized to Streamline Time-to-Market

A FUSION imaging solution can be designed and configured in minutes... not hours. And FUSION's modular offering of universally interchangeable components means your prototype is in place in days... not months.

Configured to Your Application

Using standard FUSION Lens matrix components, Qioptiq has the optical design prowess and manufacturing expertise to incorporate virtually any optical microscopy feature into your Optem FUSION Lens System. Specialized components and custom-tailored configurations are simple, expedient and cost effective.



UNMATCHED MODULAR IMAGING FLEXIBILITY

- Configure for versatile 7:1 or 12.5:1 zoom optics or for a wide range of economical fixed magnifications
- Plug-n-play system controller ensures seamless integration of motorized zoom, focus and illumination
- NOW, Optem FUSION enables extreme broadband imaging support across the visible and SWIR wavebands (400 nm - 1700 nm)
- Swap out lower lenses or LWD objectives to configure a wide range of imaging envelopes
- Interchange Camera Mounts and Camera Tubes to optimize sensor coverage for virtually any camera format or mount
- Integrate coaxial or ringlight LED illumination and automate focus and/or zoom with stepper motors
- Incorporate accessories at virtually any point of the lens assembly
- Space-efficient inline multi-point mounts ensure added imaging stability

FUSION Flexibility...

At the heart of FUSION's extreme versatility, now with SWIR compatibility, is the simplicity of stacking a variety of modules to affect magnification, function and form of the lens system.

Following are the basic required components of a functional FUSION lens assembly. From here, features and accessories are easily swapped in to meet your requirements.

Modular design allows FUSION to evolve quickly and easily

With a simple change-out of a few modules, you can modify FUSION performance, form and function to meet the evolving requirements of your system. This streamlines prototyping stages and aids the evolution of your system. Refer to the page opposite for an example of the modular changeout flexibility Optem FUSION presents.

Camera Mount

Mates FUSION with C, CS, F, EOS, 4/3-mount cameras and more

Camera Tube

Modifies magnification to your camera optimizing chip coverage & performance

Core Optical Module

Determines optical function: Fixed, 7:1 or 12.5:1 zoom magnification— motorized or manual

Lower Function Module

Integrates internal focus—motorized or manual—and coaxial LED illumination options


Lower Lens

Modifies taking magnification to affect field of view, NA and working distance




Assemble a basic Fixed-Magnification lens configuration

Vary Camera Tube and Lower Lens magnifications with the Fixed Aperture Block to yield a wide range of fixed-imaging lens configurations.




Change out core optical modules to integrate Zoom Imaging

Replace the Fixed Aperture Block with a 7:1 or 12.5:1 Zoom Module to introduce variable magnification imaging.




Integrate Lower Function Modules to add Focus and/or Coaxial Illumination

Swap out Basic Lower Function Module to integrate 15mm Fine Focus, integrated Coaxial Illumination or 5mm Focus with Coaxial Illumination.




Motorized Zoom and Focus Modules for streamlined integration of automation

Swap out Manual Zoom Modules and Fine Focus Lower Function Modules with stepper motorized modules. Digital, Multi-function Controller affords programmable control of all zoom, focus and illumination.




Introduce 90° Mirror Cubes and 50/50 Cubes to modify form and function

If you have special constraints, integrate Mirror Cube Modules at any point of the lens assembly to introduce rotatable 90° and 180° turns in the optical path. Combine with 50/50 Cubes to incorporate multiple imaging functions and/or cameras.



Streamline lens mounting and ensure imaging stability and centration

Infinity Optics afford placement of inline mounting blocks at most any point of the lens system. Ensures maximum imaging stability and solid centration repeatability even in gimbal systems.



FUSION Features...

Optem FUSION is engineered to deliver unprecedented configuration and performance flexibility. A wide array of interchangeable components affords OEMs with forward flexibility to evolve imaging capability with the life cycle of their system, and affords researchers with quick swap-out flexibility for benchtop video microscopy applications.



Extreme Imaging Versatility
FUSION delivers three distinct optomechanical capabilities within a single Lens System. Specify economical Fixed Magnification imaging modules or 7:1 and 12.5:1 Zoom Optical Modules to meet your exact micro-imaging needs. Infinity Optics and uniform fitting components streamline swap-out and maximize flexibility in the development and forward evolution of your system.



Tunable Lens Module
Space saving liquid lens module provides fast autofocus capabilities without cumbersome motorized focus drives. Simply inserts directly above the chosen Lower Function Module.



The FUSION of Simplicity and Flexibility

Designed to meet the evolving needs of today's micro imaging applications in OEM systems, the Optem® FUSION Lens System combines a uniform mechanical interface with bi-directional infinity optics to deliver unmatched interchangeability, performance versatility and functional flexibility. Improve your image and streamline your development time... specify Optem FUSION to integrate Extreme Imaging Versatility.

Fixed Magnification

MINIMUM CONFIGURATION

Magnification	0.16X
NA	0.005
Resolution	15.0 lp/mm
Depth-of-Field	23 mm
Field-of-View*	41 x 55 mm
Working Distance	490 mm

MAXIMUM CONFIGURATION

Magnification	12X
NA	0.18
Resolution	540 lp/mm
Depth-of-Field	0.018 mm
Field-of-View*	0.55 x 0.73 mm
Working Distance	32 mm



Fluorescence Imaging

Two modules utilizing user supplied Zeiss type 91029 cubes. Lower module provides system fluorescence illumination and imaging. The upper module will allow two different wavelengths to be directed to separate cameras.



Futura+ High Speed Zoom

Replace the standard 12.5:1 FUSION core zoom module with NEW Futura+ for increased speed and durability. Futura+ travels through the entire zoom range in less than 1sec and offers service life in excess of 1 -million cycles. Motorization and control is already built in.

SWIR Compatibility

When the most detailed information is critical to your application, broad 400nm - 1700nm wavelength support facilitates multi-modality imaging and is perfect for advanced imaging techniques including hyperspectral imaging and image fusion.



Seamless Motorization

The unified system controller ensures seamless integration of motorized zoom, focus and illumination for high-throughput applications. Featuring an intuitive GUI and feature-rich SDK.



Image Stable Design

Enlarged barrel diameters and wall thickness combine with a 3-point dovetail coupling interface to promote robust lens assembly. Additionally, low profile, Inline Mount Blocks allow multiple mounting points along the assembly length to ensure maximum integration stability.



Achieve Higher Magnification

FUSION is optimized to image through Optem Long-Working Distance Objectives. Select from 2X to 50X in High-Resolution and M-Plan APO and Objectives.

Optomechanical Flexibility

Integrate 90° Mirror Cubes and 50/50 Cubes at most any point along the optical path to modify the shape and fit of FUSION to your specific integration requirements. Combinations of multiple Cube Modules permit multiple cameras and lens functions to be integrated over a single optical subject.



7:1 ZOOM MAGNIFICATION

MINIMUM CONFIGURATION	LOW ZOOM	HIGH ZOOM
Magnification	0.067X	0.46X
NA	0.0047	0.016
Resolution (lp/mm)	14 lp/mm	47 lp/mm
Depth-of-Field (mm)	25 mm	2.4 mm
Field-of-View* (mm)	131 x 98 mm	19 x 14 mm
Working Dist. (mm)	490 mm	490 mm
MAXIMUM CONFIGURATION	LOW ZOOM	HIGH ZOOM
Magnification	5X	35X
NA	0.047	0.16
Resolution (lp/mm)	142 lp/mm	465 lp/mm
Depth-of-Field (mm)	0.25 mm	0.024 mm
Field-of-View* (mm)	1.7 x 1.3 mm	0.25 x 0.19 mm
Working Dist. (mm)	32 mm	32 mm

12.5:1 ZOOM MAGNIFICATION

MINIMUM CONFIGURATION	LOW ZOOM	HIGH ZOOM
Magnification	0.045X	0.55X
NA	0.0036	0.019
Resolution (lp/mm)	11 lp/mm	58 lp/mm
Depth-of-Field (mm)	44 mm	1.5 mm
Field-of-View* (mm)	196 x 147 mm	16 x 12 mm
Working Dist. (mm)	490 mm	490 mm
MAXIMUM CONFIGURATION	LOW ZOOM	HIGH ZOOM
Magnification	3.4X	41X
NA	0.036	0.19
Resolution (lp/mm)	108 lp/mm	576 lp/mm
Depth-of-Field (mm)	0.44 mm	0.015 mm
Field-of-View* (mm)	2.6 x 1.9 mm	0.21 x 0.16 mm
Working Dist. (mm)	32 mm	32 mm

* - All field-of-view data calculated for 2/3" camera



+1 503 439 6446

+1 800 668 8752
USA and CAN

2545 Railroad Street, Suite 300
Pittsburgh, PA 15222
United States

excelitas.com
Optem.info@excelitas.com

For a complete listing of our global offices, visit www.excelitas.com/locations

©2025 Excelitas Technologies Corp. Optem® is a registered trademark of Excelitas Technologies Corp. The Excelitas logo and design are registered trademarks of Excelitas Technologies Corp. All other trademarks are the property of their respective owners, and neither Excelitas Technologies Corp., its affiliates or subsidiaries, or any of their respective products, are endorsed or sponsored by or affiliated in any way whatsoever with those organizations whose trademarks and/or logos may be mentioned herein for reference purposes. Excelitas Canada Inc. reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.

Optem FUSION Brochure_2025.09